

Ultra High Performance Unvented Indirect Hot Water Cylinder

EUHPC30045V-FR-RH


Product Description

Element Pro Ultra High Performance unvented hot water cylinders are built to a high standard of quality and are manufactured from high grade duplex stainless steel. The standard operating pressure of the Element range starts at 4.5 bar, with 6 bar available where required, and Inlet and outlet connections are 28mm as standard allowing high flow rates of up to 77 l/min – a high pressure, high flow solution. The Pro range also features an up-rated primary coil to offering very fast re-heat times.

The Element PRO Indirect cylinders are supplied as standard with a combination inlet valve (incorporating pressure reducing valve, safety relief valve, balanced cold water connection, and non-return valve), a factory-fitted temperature and pressure relief valve, 1 x 6kW back-up immersion heater, secondary return connection, two port motorised zone valve and a suitably sized expansion vessel providing a complete package for your installation.

Dimensions

Height (H)	1320 mm
Outer Diameter (D)	750 mm
Weight	57 kg



ErP Rating

B

Approx Coil Surface Area (m ²)	Approx Coil Volume Area (m ²)	Recommend-ED Flow rates through Coil. (l/s)	Coil Pressure Drop-At Recommended Flow (kpa)
2	9.5	0.47	30

- Approvals: CE, UKCA, WRAS, ISO
- Building Standards: BS 853-1-1996 & BS-12-897
- Building Regulations: Part G & L
- Guarantee: internal cylinder 25 years. Ancillary components 1 year



PRODUCT DATA SHEET



Specification

Inlet connection size	28 mm
Outlet connection size	28 mm
Secondary Return Connection	1/2" BSP
Immersion Heater	1 x 6kW lph
Insulation Thickness	75 mm
Volume (Nominal)	300 ltrs
Pressure Range	4.5 bar
Expansion Vessel	50 ltrs
Heat Loss	1.55* kWh/24hr @ 65°C
Reheat Time**	13 mins
Coil Rating*	54 kW
Coil Diameter	DN25

*Based on primary flow / return temp of 80/60 °C

**Based on 70% draw-off at ΔT 45°C.

DUTYPOINT 
www.dutypoint.com

Document # DOC-15049-000

Revision : 1