

Potable water expansion vessels for use in domestic and commercial sealed chilled and hot water systems.






Advantages

- Nitrogen gas filling for longer retention of pre-pressure.
- The thread of the system connection is uncoated, ensuring problem free connection.

Technical Specifications

- Maximum working pressure: 10 bar.
- Vessels in accordance with EN13831.
- Suitable for systems with a maximum system temperature of 110 °C.
- See article webpage for the minimum/maximum temperature of the diaphragm.
- All welded construction.
- Stainless steel flange.
- Diaphragm: EPDM.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- In accordance with Pressure Equipment Directive 2014/68/EU.
- White (RAL 9010) epoxy powder coating.
- Flofix 35 - 150: Standard equipped with legs.



Type	Capacity [l]	Max. working pressure [bar]	Pre- charge [bar]	Dimensions				Syst. conn. (E)	Weigh t [kg]		Order Code
				A [mm]	B [mm]	Ø C [mm]	D [mm]				
Flofix - UK 8/2.7 [10bar]	8	10	2.7	235	272	-	-	G $\frac{3}{4}$ " M	3.0	105	25790
Flofix - UK 12/2.7 [10bar]	12	10	2.7	235	363	-	-	G $\frac{3}{4}$ " M	3.3	90	25791
Flofix - UK 18/2.7 [10bar]	18	10	2.7	290	375	-	-	G $\frac{3}{4}$ " M	4.7	60	25792
Flofix - UK 25/2.7 [10bar]	25	10	2.7	290	479	-	-	G $\frac{3}{4}$ " M	5.8	48	25793
Flofix - UK 35/2.7 [10bar]	35	10	2.7	390	482	330	70	G $\frac{3}{4}$ " M	9.8	24	25794
Flofix - UK 50/2.7 [10bar]	50	10	2.7	390	607	330	70	G $\frac{3}{4}$ " M	11.1	15	25795
Flofix - UK 80/2.7 [10bar]	80	10	2.7	390	854	330	70	G $\frac{3}{4}$ " M	13.8	15	25796
Flofix - UK 100/2.7 [10bar]	100	10	2.7	550	630	440	70	G $\frac{3}{4}$ " M	16.5	8	25797
Flofix - UK 150/2.7 [10bar]	150	10	2.7	550	837	440	70	G $\frac{3}{4}$ " M	22.0	8	25798

KIWA UK and WRAS only applicable for Flofix UK articles



Find more information online:

[Installation and operating instruction](#)
[EU Declaration of conformity PED Module A](#)
[EU Declaration of conformity PED Module D1](#)
[ACS certificate Flofix 8-150 l](#)
[Flofix 8-150L 4 bar DWG](#)
[Flofix 8-150L 4 bar STEP](#)
[Flofix 8-150L 4 bar RFA](#)
[Flofix UK 8-150L 2.7 bar DWG](#)
[Flofix UK 8-150L 2.7 bar STEP](#)
[Flofix UK 8-150L 2.7 bar RFA](#)
[Catalogue as PDF](#)
[Packaging data](#)

Washway Lane
UK-WA10 6PB, St Helens, Merseyside - gb

I flamco.aalberts-hfc.com/uk-en