Refix DT 200, green, expansion vessel, incl. Flowjet 1 1/4, 10 bar Article-No.:7309300



Refix DT with Flowjet 1 1/4" and integrated internal anti-legionella circulation, vessel for drinking water applications, water heating, water supply and pressure booster systems.

Built and tested according to EN 13831 respectively DIN-DVGW. Approval according to 2014/68/EU directive for pressure equipment.

- -replaceable butyl-bladder, build according to EN 12831, KTW-C and DVGW-W 270 standards.
 -outer/inner coating, inner coating according to KTW-A (food quality regulations).
- -Vessels stand vertical with steel profile feet -pressure gauge integrated in gas

Merkmale

compartment.

Type: DT 200 Nominal volume: 200 I Useful volume max.: 150 I perm. operating temp.: 70 °C perm. op. overpressure: 10 bar Gas inlet press ex works: 4 bar

Diameter: 634 mm Height: 973 mm Net weight: 37 kg

System connection: 2*Rp 1 1/4 Nominal flow volume: 7,2 m³/h

Colour: grün



22.09.2017 14:41

Gersteinstraße 19 • 59227 Ahlen, Germany • Postfach 2261 • 59210 Ahlen, Germany • Tel.: + 49 2382 7069-0 • Fax: + 49 2382 7069-588 • www.reflex.de Geschäftsführer: Norbert Hülsmann, Volker Mauel